

• B8103 •



Fabric		100% PES 1100 dtex	
Weight		650 g/m ²	DIN EN ISO 2286-2
Characteristics		ABUV	
Lacquering		1/1	
Comment		SIOFLUO	
Embossing		Glossy	
Breaking strength	Warp Weft	2500 N/5cm 2300 N/5cm	EN ISO 1421-1
Tear strength	Warp Weft	250 N 200 N	DIN 53 363
Adhesion		100 N/5cm	EN ISO 2411
Temperature resistance		-30/+70°C	DIN EN 1876-2
Light fastness	(except white and (half-) transparent)	7-8	ISO 105 B02
Fire behavior		M2 B1	NFP 92 507 DIN 4102
Reaction to fire		B-s2, d0	EN 13 501-1
Application		Tent & TA / Roof /Plain	

COLOR	RAL	WIDTH (cm)	
		218	□ S
		250	□ S
		300	□ S
1021	1021	□	S
1932	-	□	S
3016	-	□	S
6001	-	□	S
5007	-	□	S
5031	5010	□	S
5029	-	□	S
7001	-	□	S
7244	7043	□	S
7999	-	□	S
SILVER	7500	□	S
	9006	□	S
	9909	□	S

S=STANDARD

- NS=This is not a standard product.
Only on request. Minimum 1.000LM